



SCHEDULE 40/80 PVC FITTINGS

Spears Manufacturing

Schedule 40/80 PVC Fittings

Spears Schedule 40 and 80 PVC Fittings designs combine years of proven experience with computer-generated stress analysis to yield the optimum physical structure and performance for each fitting. Material reinforcement is uniformly placed in stress concentration areas for substantially improved pressure handling capability. Resulting products are subjected to numerous verification tests to assure the very best PVC fittings available.

- Comprehensive line of PVC fittings from 1/4" to 12" sizes
- Schedule 40 sizes conform to ASTM D 2466
- Schedule 80 sizes conform to ASTM D2467 and Spears' exclusive CL150 Flanges in sizes 1/2" through 16"
- Exceptional chemical and corrosion resistance
- High temperature ratings allow a wide range of process applications
- Lower installation costs
- Higher flow capacity
- All PVC Schedule 40 and 80 fittings shall be produced by Spears Manufacturing Company from PVC Type 1 cell classification 12454, conforming to ASTM D 1784.
- All injection-molded PVC Schedule 40 and 80 fittings shall be certified for potable water service by NSF International and manufactured in strict compliance to ASTM D 2466 and 2467, respectively.
- All fabricated fittings shall be produced in accordance with Spears General Specifications for Fabricated Fittings.